

Tel: 01327 311011
FAX: 01327 300216
Email: sales@kaver.co.uk
Web: www.foxstandpipes.co.uk

foxstandpipes
9-11 Siddeley Way
Royal Oak Estate
Daventry
Northants
NN11 8PA



FOX Pillar

Standpipe Enclosure



The FOX Pillar standpipe enclosure provides a robust and flexible solution for the installation and protection of standpipe and washdown facilities.

FOX pillars are used by water companies throughout the UK. A quality and cost effective solution frequently specified for new build and upgrade applications.

Key Features

- Quality GRP construction with UV stable gel coat finish
- Generous access door with quarter turn security latch fitted as standard
- **1/2" or 3/4" hose union tap fitted with in-line double check valve and insulated MDPE plumbing to suit**
- Installed height 1.1m (part buried) or 1.5 m (surface installation with lower access door).
- Readily configured to customer requirements, isolation valve, drain valve, multi-tap etc.



Bottom hinged access door as standard, side hinged as option

Lower access door can be fitted for valve access / surface installation



1/2" or 3/4" hose union tap fitted as standard with in-line double check valve and insulated MDPE pipe work to suit.

FOX Pillar

Standpipe Enclosure

Detailed Description:

FOX pillar standpipe enclosure. FRP construction using Lloyds approved materials and finished with UV stable Olive Green gel-coat. Bottom hinge access door fitted with 1/4 turn latch to **accept padlock (not supplied), side hinging available as option. Fitted with BS1010 DZR 1/2" or 3/4" hose union bib tap, insulated MDPE pipe work to suit with in-line double check valve.** Iso-lation valve can be fitted as option. Lower access door available as option, recommended if surface installation required. Specification readily adapted to customer requirements.

The installer is responsible for ensuring the suitability of the specification for the application.

Standard parts, alternative configuration on request:

Part No.	Description
FP001	FOX Pillar, Single piece FRP body with Olive Green gel-coat finish, bottom hinge access door with 1/4 latch to accept padlock (not supplied), Housing Only
FP050	As above with 1/2" hose union tap, in-line double check valve, insulated 20mm MDPE pipe work
FP075	As above with 3/4" hose union tap, in-line double check valve, insulated 25mm MDPE pipe work
-AD	Lower access door option—must be specified at time of ordering

Dimensions:

